

标准尺寸适配器和衬套

由 Foxit PDF Editor 编辑
版权所有 (c) by Foxit Software Company, 2003 - 2009
仅用于评估。



适配器



- ✓ 坚固的设计
- ✓ 提供不锈钢、黄铜或碳钢材质
- ✓ 减至 1/8 NPT
- ✓ 适配最高 1 NPT

NPT 螺纹		对六角平头 (英寸)	长度 (英寸)	材料	
外螺纹	内螺纹			黄铜 型号	不锈钢 型号
缩小型适配器					
1/8	1/4	1 1/8	1.50	RA-18-14-BR	RA-18-14-SS
1/8	1/2	1 1/8	1.50	RA-18-12-BR	RA-18-12-SS
1/4	1/2	1 1/8	1.69	RA-14-12-BR	RA-14-12-SS
7/16-20	1/4	1 1/8	1.94	—	RA-716-14M-SS
1/2	3/4	1 3/8	1.94	RA-12-34-BR	RA-12-34-SS
1/2	1	1 5/8	2.16	—	RA-12-1-SS
缩小型衬套					
1/4	1/8	7/8	1.09	RB-14-18-BR	RB-14-18-SS
1/2	1/8	7/8	1.09	RB-12-18-BR	RB-12-18-SS
1/2	1/4	7/8	1.09	RB-12-14-BR	RB-12-14-SS
3/4	1/2	1 1/8	1.17	RB-34-12-BR	RB-34-12-SS
1	1/2	1 3/8	1.36	RB-1-12-BR	RB-1-12-SS
1	3/4	1 3/8	1.36	RB-1-34-BR	RB-1-34-SS
1 1/4	3/4	1 3/4	1.48	—	RB-114-34-CS*
1 1/4	1	1 3/4	1.48	—	RB-114-1-CS*
1 1/2	1	2	1.56	—	RB-112-1-CS*

压合接头 OMEGALOK®



- ✓ 正压力密封件套圈设计
- ✓ 不锈钢或黄铜的坚固耐用结构
- ✓ 用于 1/16 ~ 1/2" 的保护管径

* 仅提供碳钢接头。

订购示例: RB-12-14-SS, 不锈钢 1/2" 外螺纹到 1/4" 内螺纹缩小型衬套。

备用套圈— (10件装)

保护管 外径	黄铜	不锈钢	PTFE ₊
1/16"	B-FER-1/16	SS-FER-1/16	T-FER-1/16
1/8"	B-FER-1/8	SS-FER-1/8	T-FER-1/8
3/16"	B-FER-3/16	SS-FER-3/16	T-FER-3/16
1/4"	B-FER-1/4	SS-FER-1/4	T-FER-1/4
5/16"	B-FER-5/16	SS-FER-5/16	T-FER-5/16
3/8"	B-FER-3/8	SS-FER-3/8	T-FER-3/8
1/2"	B-FER-1/2	SS-FER-1/2	T-FER-1/2

†PTFE只能与不锈钢压合接头配合使用。

保护管 外径 (英寸)	外螺纹 NPT	长度 mm (inch)	黄铜 型号	316不锈钢 型号
1/16	1/16	24.6 (0.97)	N/A	SSLK-116-116
1/16	1/8	26.2 (1.03)	BRLK-116-18	SSLK-116-18
1/8	1/8	30.0 (1.18)	BRLK-18-18	SSLK-18-18
1/8	1/4	44.2 (1.74)	BRLK-18-14	SSLK-18-14
3/16	1/8	31.0 (1.22)	BRLK-316-18	SSLK-316-18
3/16	1/4	46.0 (1.81)	BRLK-316-14	SSLK-316-14
1/4	1/8	32.8 (1.29)	BRLK-14-18	SSLK-14-18
1/4	1/4	37.6 (1.48)	BRLK-14-14	SSLK-14-14
5/16	1/4	39.1 (1.54)	N/A	SSLK-516-14
3/8	1/4	40.4 (1.59)	BRLK-38-14	SSLK-38-14
3/8	3/8	40.4 (1.59)	BRLK-38-38	SSLK-38-38
3/8	1/2	46.0 (1.81)	BRLK-38-12	SSLK-38-12
1/2	1/2	49.3 (1.94)	BRLK-12-12	SSLK-12-12

订购示例: BRLK-18-18, 黄铜 1/8 NPT 压合接头, 用于 1/8" 外径保护管。
SSLK-14-14, 316SS 1/4 NPT, 用于 1/4" 外径保护管的压合接头。